# Photo Papers



# 6062B Glossy Photo Paper FSC® $240 \text{ g/m}^2$

Product This top quality photo inkjet paper has a quality photo coating for high grade natural colour prints of Description graphic pictures, presentations and photos. The paper is instant dry, is smudge resistant and provides good colour density and excellent image sharpness. This paper is compatible with a large range of dye and pigment digital printing systems, and is the most ideal product for users who need top quality photographic re-productions.

### Physical **Properties**

Thickness	245 μ <b>m</b>	ISO 534
Weight	240 g/m2	ISO 536
Colour I *: a*: b*)	95.5: 0.95:-7.57	DIN 13655

Opacity 97% ISO 2471 Gloss 75o 73% ISO 21974 Curl at 23oC, 50% RH 0

All values, isted are target values

# Applications/ Photography features

Portraits Posters Graphic art reproductions Exhibition graphics

Indoor and Outdoor Signage Instant Dry High Whiteness Good Colour Density

High sharpness Smudge and water resistant Lamination not necessary Excellent lay-flat FSC certified

### Available Widths (mm)

3" core incl 432 610 914 1067 2" adaptors

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Store paper only in original boxes, out of direct sunlight and under normal climatic conditions Conditions (23 °C, 50% RH) until ready to use. Allow material to adapt to room conditions before use. Papers can absorb moisture in humid conditions or lose moisture in low humidity conditions. Highly humid conditions make the ink drying time longer and this could interfere with proper laminate adhesion.

# Environment. Health & Safety

No Material Safety Data Sheet required.

#### Lamination Compatibility

Cold	Warm	Hot
yes	Yes	no

Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C

Shelf life

Two years from shipping date when stored under ideal conditions (see above)

Colour Canon develops high-quality colour profiles for media / ink / printer / RIP combinations. Profiles Check availability of profiles for your printer on www.canon-europe.com/mediaguide

# Environmental Certifitcation





# Processing Guidelines

### **Printing guidelines**

Allow material to adapt to room conditions for 24 hours before printing. Side to be printed is the outer side of the roll.

Make sure that the media comes not into contact with grease, oil, silicon, and dirt to avoid printing defects. It is recommended to handle the media with cotton gloves.

Insert the paper with care in the printer. Incorrect loading can cause skewing or creasing. It is recommended to calibrate the printer before printing and to make a test print.

Print results will vary for different printer ink combinations. Ink restrictions and printer settings should be set for specific printer-ink combinations to obtain the best results.

Canon media profiles include optimal ink and printer settings for Canon supported printers. Depending on fluctuations in environment, printer, ink, media and applications, printer parameters may have to be adjusted slightly, to obtain the best results.

The use of dye inks can lead to premature fading of colors.

Recommended media settings on Canon printers: Operation Panel: GlossyPhoto 240g Printer Driver: Canon Glossy Photo Paper 240gsm

# Application guidelines

To add surface protection from dirt, abrasion and gas-fading, lamination is recommended. Although ink drying is virtually immediate, it is still recommended to allow a waiting time of approximately 3 hours before lamination. In order to prevent moisture ingress and paper splitting, lamination with a 5-6 mm encapsulated edge is also recommended.

Laminate must be evenly applied to the print in order to avoid curling. Both warm and cold lamination is possible.

Standard disclaimer: All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc. canon.com Canon Europe canon-europe.com English edition 0615 © Canon Europa N.V., 2024

